



MARK ,Π ୍ଦ୍ର ŢΠ ٦ \triangleright 2"X3" | UL JACKETED DIM 2; 2, LABEL SCH 40 MONITOR ACCESS TUBE NPT SUBMERSIBLE TURBINE PUMP TANK GAGE NPT FITTING W/ 2" NPT AUTOMATIC OPTIONAL NPT FITTING NPT VENT NPT FILL DESRIPTION

FITTING SCHEDULE

Plasteel® Elutron® Jacketed Tank

8,000 GALLONS CAPACITY 30,400 LITERS

EMPTY WEIGHT ~ 7,400 LBS / 3,360 KILOGRAM

- I. TANK MUST BE UL LISTED AND LABELED JACKETED PER UL Standards 58 and 1746, Part III.
- TANK MUST BE INSTALLED PER THE PLASTEEL TANK MANUFACTURER'S INSTALLATION INSTRUCTIONS.

 TANK MUST COMPLY WITH THE REQUIREMENTS OF THE

2

- 3. TANK MUST COMPLY WITH THE REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION.
- 4. WEIGHTS AND DIMENSIONS ARE APPROXIMATE. CONSULT WITH YOUR PLASTEEL® TANK MANUFACTURER FOR SPECIFIC WEIGHTS AND DIMENSIONS.

 5 THREADED CONNECTIONS ARE TYPICAL. PIPING CONTAINMENT SUMP ATTACHMENT COLLARS ARE OPTIONAL. CONSULT WITH YOUR PLASTEEL® TANK MANUFACTURER FOR DETAILS AND
- 6. TANK VENT FITTING SIZE MUST COMPLY WITH UL STANDARD 58.



